


PROCLAIM[®]

CONCRETE FLOOR COATING



Available Packaging



The Proclaim Difference

Proclaim Concrete and Terrazzo Floor Coating is ideal for warehouses, manufacturing plants, loading and staging areas, retail facilities, and hard surface areas that get heavy traffic from forklifts, pallet jacks, rolling carts and other heavy equipment. **Proclaim's** high gloss and durability will add quality to your facility's overall floor care program, and it is U.L. Classified for slip resistance to provide better safety for employees.



FEATURES

- High gloss
- Non-yellowing
- Responds well to burnishing
- Easy to apply
- Great adhesion
- Non-powdering
- Dries quickly
- U.L. Classified for slip resistance
- Makes floors easier to maintain
- Allows for more efficient dust mopping
- Water-based, urethane fortified acrylic system

PROCLAIM[®]

CONCRETE FLOOR COATING

DIRECTIONS FOR USE

FLOOR PREPARATION:

For freshly poured concrete floors, use 2 coats of Cirene as a base coat.

For previously water-based seal coated floors:

1. Strip floor thoroughly, using Buckeye **Revelation[®]** or **Juggernaut[®]** following label directions.
2. After picking up solution, apply a liberal amount of Buckeye **Sparkle** diluted at 3 oz./gal., allow to dwell for 7 to 10 minutes, scrub thoroughly and pick up.
3. Thoroughly rinse floor with plain water. Scrubbing with clean pads or a brush during this step is also recommended.
4. Allow floor to dry thoroughly before applying **Proclaim**.

APPLICATION:

1. Use a clean mop and bucket or applicator.
2. Saturate a clean mop and press firmly into wringer to remove excess **Proclaim**. Do not wring mop.
3. Apply **Proclaim** using an overlapping figure-eight motion. NOTE: The first coat on porous floors should be applied medium to heavy.
4. Allow to dry (usually 30 to 40 minutes). Temperature, humidity and air movement affect dry time.
5. Apply additional coats until desired gloss is achieved. Apply no more than four (4) coats in a 24-hour period.
6. Allow **Proclaim** to properly cure for 48 hours before scrubbing.

MAINTENANCE:

1. Dust mop floor.
2. Damp mop or autoscrub floor as needed, using Buckeye **Crossbow[®]**, **Straight-Up[®]** or **Buckeye Blue**. Extremely soiled surfaces may require the use of Buckeye **Two-O-One[™]** or Buckeye **Ambush[™]**.
3. Top scrub and recoat as needed.

TECHNICAL SPECIFICATIONS

pH	7.4 – 7.8
Weight/Gallon	8.59 lbs
Freeze-Thaw Stability	Passes 3 Cycles
Removability	Excellent
Slip Resistance	UL Classified



For more information about Proclaim, scan this code.



BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com