



Available Packaging



FEATURES

- Superior response to burnishing
- Zinc-free
- High gloss
- Green Seal[™] certified
- Non-yellowing
- Non-powdering
- Ammonia-free
- U.L. listed
- Easy to repair and maintain

The Verde Ultra Difference

When you want the greatest response to burnishing, **Verde Ultra** Floor Finish quickly builds to a radiant gloss. Each time you burnish **Verde Ultra**, you will achieve a more brilliant shine and enhanced durability. Designed for green floor care programs, **Verde Ultra** also meets the most stringent environmental standards without sacrificing product performance.



This product meets Green Seal[™] Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

DIRECTIONS FOR USE

FLOOR PREPARATION:

- 1. Strip floor using Buckeye **Penetrate™**, Buckeye's Green Seal® certified floor stripper.
- 2. After picking up solution, rinse floor until no residue remains.
- 3. Allow floor to dry before applying Verde Ultra.

APPLICATION:

- 1. Use a clean mop and bucket.
- 2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.
- 3. Apply finish in even coats.
- 4. Allow each coat to dry, usually 20 to 30 minutes.
- 5. Apply multiple coats until desired gloss is achieved.

MAINTENANCE:

- 1. Dust mop floor.
- 2. Damp mop floor as needed, using Buckeye $\textbf{Tenacity}^{\circledast}, \textbf{True 7}^{\texttt{Tw}}$, or other Buckeye cleaner.
- 3. Burnish as needed.

Note: Ensure adequate ventilation, especially in confined areas.

TECHNICAL SPECIFICATIONS	
рН	7.6 ± 0.2
Leveling	Excellent
Freeze/Thaw Stability	Pass Three Cycles
Removability	Excellent
Drying Time	20–30 minutes
Black Mark Resistance	Very Good
Film Color	Clear
Weight/Gallon	8.55 lbs
Slip Resistance	UL Classified

For more information about Verde Ultra, scan this code.



BUCKEYE INTERNATIONAL, INC. 2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583 www.buckeyeinternational.com

2565 (9/17)