

BASE HIT™

Base Hit Baseboard Stripping Gel removes floor finish buildup and heavy soils from baseboards, resilient tile and hard-surface flooring.

- * **Product produced under one or more of the following U.S. Patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341; 5,849,682. Canada Patents: 2,056,425; 2,080,352; 2,057,027. Other patents pending.**
- * **Penetrates and emulsifies stubborn floor finish buildup**
- * **Clinging gel sticks to vertical surfaces**
- * **More strength than conventional strippers for additional labor savings**
- * **Easy-rinsing/non-filming**
- * **Fresh Fragrance**
- * **Packaging in large 23 oz. aerosol can for economy and convenience**

Directions for use:

1. Shake well before and during use.
2. Test surface to be cleaned to determine if any change in color or texture of surface will result from its use.
3. Do not spray painted surfaces.
4. Hold can UPSIDE DOWN 6-10 inches from surface to be sprayed. Cover surface with a thin, even coating. Wipe off any over-spray immediately.
5. Wait 3 to 5 minutes (longer in case of severe buildup).
6. Scrub with a doodle bug pad or stripping pad.
7. Rinse with clean water.

Caution: May cause eye and skin irritation. Contents under pressure. Use in upside down position only! Temperatures over **120°F (50°C)** may cause bursting. Do not puncture or incinerate, or use near open flame. Intentional misuse by concentrating and inhaling contents may be harmful or fatal. Avoid eye and skin contact.

For Industrial and Institutional use only.

Buckeye®

BASE HIT™

BASEBOARD STRIPPING GEL



WARNING:
CONTENTS UNDER PRESSURE
SEE BACK PANEL FOR FURTHER PRECAUTIONS
NET WT. 23 OZ. (.66 Kg)

Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • (314) 291-1900

www.buckeyeinternational.com

1786 (4/08)