



# REVELATION<sup>®</sup>

## UNIVERSAL COLD WATER STRIPPER



- **Contains Patented Liquescent<sup>®</sup> Technology for Extra Power and Safety**
- **Contains NO Butyl** - typically known as 2-butoxyethanol or ethylene glycol monobutyl ether, CAS# 111-76-2
- **Safer for Environment** - does not require reporting under SARA Title III Section 313'
- **Works in COLD Water**
- **Liquefies Finish and Seal** - lower incidence of pad clogging, easy pad cleaning
- **Versatile** - effectively strips acrylic seals, water-based urethanes and polymer floor finishes
- **Labor Saver** - strips the first time, most strippers require additional applications
- **Highly Concentrated** - for economical end-use dilutions
- **Does Not Release Noxious Vapors**
- **For Use on Resilient Tile and Hard Surface Flooring**



**Buckeye Revelation®** is a totally new concept in stripping technology for removing both floor finishes and sealers. You will be amazed by its effectiveness and delightfully pleasant fragrance.

**Revelation's** butyl-free formulation can be used on all industrial flooring (resilient tile, terrazzo, marble, concrete, rubber, etc.) to remove floor finish and/or both floor finish and sealer. A 1:10 dilution of **Revelation** removes finish only. **Revelation** diluted at 1:4 is tough enough to remove finish, acrylic seals and water-based urethane concrete sealers.

**Buckeye Revelation** is highly effective and economical. **Revelation** works in COLD water, making strip jobs easier and more efficient.

This product is produced under one or more of the following U.S. patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341 and 5,849,682. Canadian patents: 2,056,425, 2,057,027 and 2,080,352; 2,057,027. Other patents pending.

Recommended for use with Buckeye's Patented Action Control System® II. For stripping normal to heavy floor finish buildup: Use the **Green Action Lock II Connector™** for removing finish and seal, use the **Grey Action Lock II Connector**.



## Directions for Use

### For Removing Floor Finish:

Use 12 fl. oz./gallon COLD water (100 ml/l), (1:10).

1. Wet floor with **Revelation** solution. Allow to stand 10 minutes.
2. Machine scrub.
3. Pick up solution. Do not allow to dry on floor.
4. Rinse floor at least twice with cold water.
5. After floor is dry, apply finish.

### For Removing Sealer:

Use 32 fl. oz./gallon COLD water (250 ml/l), (1:4).

1. Wet floor with **Revelation** solution. Allow to stand 15 minutes. Follow steps 2-5 above.



Available in:



## Technical Specifications

Total Actives	45.6%
pH Concentrate	12.0 + 0.2
pH (1:4)	11.5 + 0.2
pH (1:10)	11.1 + 0.2
Weight/Gallon	8.40
Flash Point	None to Boiling
Color	Bright Red
Odor	Rose Floral
Hard Water Stability (1:80 with 350 ppm hard water)	Clear
Rinsing Properties	Excellent
Freeze/Thaw Stability	Unaffected by Freezing
Foaming Properties	Extremely Low

## Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • Missouri 63043 • 314.291.1900  
www.buckeyeinternational.com