

# PROCLAIM<sup>®</sup>



**A CONCRETE and TERRAZZO Coating  
which... PROTECTS and BEAUTIFIES**



**Proclaim** Concrete and Terrazzo Floor Coating is perfect for warehouses, manufacturing plants, loading and staging areas, or retail facilities.

**Proclaim** is ideal for hard surface areas that get heavy traffic from forklifts, pallet jacks, rolling carts and other heavy equipment.

**Proclaim's** U.L. listed slip resistance provides more safety for employees. Plus, a finished floor is easier to clean and keep dust-free!

**Proclaim's** high gloss and durability will add quality to your facility's overall floor care program.



- High Gloss
- Non-Yellowing
- Responds Well to Burnishing
- Easy to Apply
- Great Adhesion
- Non-Powdering
- Dries Quickly
- U.L. Listed for Slip Resistance
- Makes Floors Easier to Maintain
- Allows for More Efficient Dust Mopping
- Water-Based, Urethane Fortified Acrylic System

# PROCLAIM®

## Directions for Use

### Floor Preparation:

#### For freshly poured concrete floors:

1. Allow new floor to set-up 30 days to ensure proper cure.
2. Scrub floor using **Buckeye Blue** at 2 oz./gal. of cold water.
3. After picking up solution, apply a liberal amount of Buckeye **Sparkle™** diluted at 3 oz./gal., allow to dwell for 7 to 10 minutes, scrub thoroughly and pick up.
4. Thoroughly rinse floor with plain water. Scrubbing with clean pads or a brush during this step is also recommended.
5. Allow floor to fully dry before applying **Proclaim**.

#### For previously water-based seal coated floors:

1. Strip floor using Buckeye **Revelation®** or **Juggernaut®**.
2. After picking up solution, apply a liberal amount of Buckeye **Sparkle** diluted at 3 oz./gal., allow to dwell for 7 to 10 minutes, scrub thoroughly and pick up.
3. Thoroughly rinse floor with plain water. Scrubbing with clean pads or a brush during this step is also recommended.
4. Allow floor to fully dry before applying **Proclaim**.

### Application:

1. Use a clean mop and bucket or applicator.
2. Saturate a clean mop and press firmly into wringer to remove excess **Proclaim**. Do not wring mop.
3. Apply **Proclaim** using an overlapping figure-eight motion. **NOTE:** The first coat on porous floors should be applied medium to heavy.
4. Allow to dry (usually 30 to 40 minutes). Temperature, humidity and air movement affect dry time.
5. Apply additional coats until desired gloss is achieved. Apply no more than four (4) coats in a 24-hour period.
6. Do not scrub floors for 48 hours.

### Maintenance:

1. Dust mop floor.
2. Damp mop floor as needed, using Buckeye **Crossbow®**, **Straight-Up®** or **Buckeye Blue**. Extremely soiled surfaces may require the use of Buckeye **Two-O-One™** or Buckeye **Ambush™**.
3. Top scrub and recoat as needed.



### Available in:



### Technical Specifications

pH	8.0 ± 0.2
Weight/Gallon	8.59 lb
Freeze-Thaw Stability	Passes 3 Cycles
Removability	Excellent
Slip Resistance	U.L. Classified



## Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • Missouri 63043 • 314/291-1900

[www.buckeyeinternational.com](http://www.buckeyeinternational.com)