

# R.P.M.<sup>TM</sup>

## FINISH ENHANCER




- Great cleaning ability
- Outstanding response to burnishing
- Removes scratches, scuffs and black heel marks

Buckeye R.P.M. is a Realistic Professional Maintenance system designed to meet today's increasing demands for the ultra high gloss look, without being labor intensive.

R.P.M. Finish Enhancer is made for both mop-on and autoscrambling floor maintenance programs. Dilute 1:4 with water for mopping or autoscramble R.P.M. (mixed 1:10 with water) on the floor, let it dry and buff it out later. With either program, R.P.M.'s superior gloss system extends recoating intervals and keeps finish buildup to a minimum. Also, R.P.M. will not yellow on your floor.

Available in:




12x1  
Quart  
Cases



4x1  
Gallon  
Cases



5-gallon  
Action  
Pacs<sup>®</sup>



55-gallon  
drums

### Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • USA • (314)291-1900  
[www.buckeyeinternational.com](http://www.buckeyeinternational.com)

# FEATURES

Versatile - May be used with any high speed/ultra high speed buffer or propane burnisher.

Uniquely formulated - R.P.M. is a special blend of polymers designed to interact with floor finishes.

Slip resistant

Removes scratches, scuffs and black heel marks

Bonds to floor finishes to form a long-lasting durable gloss

Resistant to scuffing and black marking

Two methods of application - Mop-on or autoscrub

Dilutable - May be diluted 1:4 for mop-on method or 1:10 for autoscrubbing

Non-powdering - Will not break down under the heat generated by burnishing

## DIRECTIONS FOR USE

### FLOOR PREPARATION:

1. Use a scraper or putty knife to remove all gum, tape or other foreign material from floor.
2. Dust mop the entire floor area.
3. Damp mop or lightly autoscrub the entire floor to remove excess dirt.

### AUTOSCRUBBER APPLICATION:

1. Dilute 12 fl. oz. of R.P.M./gallon of cold water (100ml/l), (1:10) in the autoscrubber.
2. Scrub floor. When floor is dry, burnish or high speed buff.

### MOP-ON APPLICATION:

1. Dilute one quart R.P.M./gallon of cold water (250ml/l), (1:4) in a mop bucket.
2. Damp mop solution onto floor. When floor is dry, burnish or high speed buff.
3. To increase gloss, periodically spray a fine mist of water onto buffing pad.

## TECHNICAL SPECIFICATIONS

Weight/Gallon	8.4 lb
pH concentrate	7.6 ± 0.2
Solvents	None
Freeze/Thaw Stability	Pass 3 cycles
% Actives	9.5 ± 0.2
Storage Stability	Excellent*
Removability	Easily removed
Color	White/opaque



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY. 169S

\*When stored in original, unopened containers.

Classified by Underwriters Laboratories, Inc. for Floor Coatings and Finishing Materials As To Slip Resistance Only. 169S

## Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • USA • (314)291-1900  
www.buckeyeinternational.com