



* See back page

VERDE™

Environmental Floor Finish

Buckeye **Verde**™ is a Sealer/Finish designed for “green” floor care programs. All aspects of Buckeye **Verde** meet the most stringent environmental standards without sacrificing product performance.



Buckeye®



VERDE™

Environmental Floor Finish

DIRECTIONS FOR USE

FLOOR PREPARATION:

1. Strip floor using Buckeye **Penetrate™**, Buckeye's Green Seal® certified floor stripper.
2. After picking up solution, rinse floor until no residue remains.
3. Allow floor to dry before applying **Verde**.

APPLICATION:

1. Use a clean mop and bucket.
2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.
3. Apply finish in even coats.
4. Allow each coat to dry, usually 20 to 30 minutes.
5. Apply multiple coats until desired gloss is achieved.

MAINTENANCE:

1. Dust mop floor.
2. Damp mop floor as needed, using Buckeye **Tenacity®**, **True 7™**, or other Buckeye cleaner.
3. Burnish as needed.

*This product meets Green Seal's environmental standards for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential.

FEATURES

- Zinc-free
- High gloss
- Green Seal* Certified
- Non-yellowing
- Non-powdering
- Ammonia-free
- U.L. Listed
- Easy to repair and maintain

ADVANTAGES

- Satisfies low metal waste water requirement
- Presents professional image
- Meets or exceeds government specs
- Lengthens time between strip outs
- Lengthens time between strip outs
- Pleasant to work with
- Reduces slip and fall liability
- Marks and scratches buff out easily to save time

BENEFITS

- Safe for environment
- Draws compliments to maintenance staff
- Environmentally safe
- Saves labor time and cost
- Saves labor time and cost
- No harsh odor
- Provides shiny but safer working surface
- Saves labor time and cost

Available in:



TECHNICAL SPECIFICATIONS

pH	7.6
Leveling	Excellent
Freeze/Thaw Stability	Passes Three Cycles
Removability	Excellent
Drying Time	20-30 Minutes
Black Mark Resistance	Very Good
Film Color	Clear
Weight/Gallon	8.55 lb
Slip Resistance	UL Classified



Buckeye International, Inc.

2700 Wagner Place • Maryland Heights • MO 63043 • USA • 800.321.2583
www.buckeyeinternational.com