

Buckeye





Available Packaging



The Liberate Difference

Liberate is a foaming, heavy-duty cleaner/degreaser that clings to vertical surfaces as it cuts through and dissolves oils, fats, grease, grime, and soap scum.

Apply **Liberate** on floors, walls, cutting tables and processing equipment. **Liberate** may also be used in shower rooms to remove soap buildup.

DESIGNED FOR USE IN:

- Meat cutting rooms
- Processing plants
- Industrial kitchens
- Commissaries
- Restaurants

FEATURES

- Patented Liquescent[®] technology Contains patented Liquescent technology for exceptional cleaning and improved worker and environmental safety.
- Richer foaming Clings to vertical surfaces for penentrating degreasing actions.
- Faster cleaning Reduced labor costs.
- Butyl-free Contains no butyl (2-butoxy ethanol).
- No free caustic

Free caustic endangers employees (burns skin and eyes).





Nonfood Compounds Program Listed (Catergory A1) Registration #026132



DIRECTIONS FOR USE

Liberate may be applied with a foam gun. Fill the product reservoir with **Liberate**, connect the foam gun to a hot water hose, adjust the proportioning ratio, turn on the water valve on the foam gun and squeeze the trigger to dispense foam. Adjust existing foaming equipment to a dilution rate from 1:20 (6 oz./gal.) to 1:25 (5 oz./gal.) for best results.

FOAM CLEANING:

IN AREAS WITH FLOOR DRAINS

- 1. Cover or remove all food items in areas to be cleaned.
- 2. Flush thoroughly with hot water to remove surface soils.
- 3. With a foam gun or similar applicator, apply **Liberate** to all washable surfaces. Allow foam to cling at least five minutes. Repeat, if necessary.
- 4. Rinse thoroughly, using hot water. Allow surface to drain dry, tilting all movable surfaces to aid water run-off.
- 5. If surfaces require sanitizing, use **Buckeye Sani-Q**[™] according to directions.

MANUAL CLEANING/LIGHTER SOILS:

(Dilutions for **Liberate** may vary between 1:12 and 1:40, depending on soil conditions, soak time and water temperature.)

- 1. Use **Liberate** at a dilution of 1:40 (3 oz./gal of hot water). Apply by mop, brush or spray.
- 2. Allow to set on surface for several minutes and then scrub with brush or sponge.
- 3. Remove solution on floors with a squeegee, mop or wet/dry vacuum.
- 4. Rinse immediately with hot water.

To clean filters, utensils and equipment, dilute **Liberate** at 1:20 (6 oz./gal) with hot water. Soak for 15 to 20 minutes and brush or sponge as necessary. Rinse thoroughly and sanitize if required.

TECHNICAL SPECIFICATIONS	
pH Concentrate	12.7 ± 0.2
% Actives	10.5%
Weight/Gallon	8.5 lbs
Color	Water Clear
Fragrance	None
Phosphates/NTA	None
Freeze Thaw	Unaffected

SAFETY:

Wear eye protection, rubber or plastic gloves, and water or chemical resistant footwear.

BUCKEYE INTERNATIONAL, INC. 2700 WAGNER PLACE • MARYLAND HEIGHTS • M0 63043 • USA • 800.321.2583 www.buckeyeinternational.com

Product produced under one or more of the following U.S. Patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341; 5,849,682. Canada Patents: 2,056,425; 2,080,352; 2,057,027.