

Buckeye®

# R.P.M.™

## FINISH ENHANCER




### The **R.P.M.** Difference

Buckeye **R.P.M.** is a Realistic Professional Maintenance system designed to meet today's increasing demands for a ultra high gloss look, without being labor intensive.

**R.P.M.** Finish Enhancer is made for both mop-on and autoscrubbing floor maintenance programs. Dilute 1:4 with water for mopping or autoscrub **R.P.M.** (mixed 1:10 with water) on the floor; let it dry and buff it out. With either program, **R.P.M.**'s superior gloss system extends recoating intervals and keeps finish buildup to a minimum. Also, **R.P.M.** will not yellow on your floor.

#### Available Packaging



### FEATURES

- Versatile — May be used with any high speed/ultra high speed buffer or propane burnisher.
- Uniquely formulated — R.P.M. is a special blend of polymers designed to interact with floor finishes.
- U.L. listed for slip resistance
- Removes scratches, scuffs and black heel marks
- Bonds to floor finishes to form a long-lasting durable gloss
- Resistant to scuffing and black marking
- Two methods of application — Mop-on or autoscrub
- Dilutable — May be diluted 1:4 for mop-on method or 1:10 for autoscrubbing
- Non-powdering — Will not break down under the heat generated by burnishing





# R.P.M.<sup>TM</sup>

FINISH ENHANCER

## DIRECTIONS FOR USE

### FLOOR PREPARATION:

1. Use a scraper or putty knife to remove all gum, tape or other foreign material from floor.
2. Dust mop the entire floor area.
3. Damp mop or lightly autoscrub the entire floor to remove excess dirt.

### AUTOSCRUBBER APPLICATION:

1. Dilute 12 fl. oz. of R.P.M./gallon of cold water (100 ml/l), (1:10) in the autoscrubber.
2. Scrub floor. When floor is dry, burnish or high speed buff.

### MOP-ON APPLICATION:

1. Dilute one quart R.P.M./gallon of cold water (250 ml/l), (1:4) in a mop bucket.
2. Damp mop solution onto floor. When floor is dry, burnish or high speed buff.
3. To increase gloss, periodically spray a fine mist of water onto buffing pad.

TECHNICAL SPECIFICATIONS	
pH Concentrate	7.6 ± 0.2
Weight/Gallon	8.4 lbs
Solvents	None
Freeze/Thaw Stability	Passes 3 cycles
% Actives	9.5 ± 0.2
Storage Stability	Excellent*
Removability	Easily removed
Color	White/Opaque
Slip Resistance	U.L. Classified



\*When stored in original, unopened containers

### BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com