


Buckeye®

# REVELATION®

UNIVERSAL COLD WATER FLOOR STRIPPER



Available Packaging



## The Revelation Difference

**Revelation's** butyl-free formulation is highly effective and economical. **Revelation** works in COLD water, making strip jobs easy and efficient.

**Revelation** removes both floor finishes and sealers, and may be used on all industrial flooring (resilient tile, terrazzo, marble, concrete, rubber, etc.) To remove floor finish, dilute **Revelation** at 1:10. To remove heavy finish buildup, acrylic seals and water-based urethane concrete sealers, dilute **Revelation** at 1:4.



## FEATURES

- Contains Liquescent® technology for better performance and safety
- Butyl-free (2-butoxyethanol or ethylene glycol monobutyl ether CAS# 111-76-2)
- Works in COLD Water
- Liquefies Finish and Seal – lower incidence of pad clogging, easy pad cleaning
- Versatile – effectively strips acrylic seals, water-based urethanes and polymer floor finishes
- Labor Saver – strips the first time, most strippers require additional applications
- Highly Concentrated – for economical end-use dilutions
- Does not release noxious vapors
- For use on resilient tile and hard surface flooring

# REVELATION<sup>®</sup>

UNIVERSAL COLD WATER FLOOR STRIPPER

## DIRECTIONS FOR USE

**For Removing Floor Finish:**

Use 12 fl. oz./gallon cold water (100 ml/L), (1:10).

1. Wet floor with **Revelation** solution. Allow to stand 15–25 minutes on the floor depending on the number of coats needed to be removed.
2. Machine scrub.
3. Pick up solution. Do not allow to dry on floor.
4. Rinse floor at least twice with cold water.
5. After floor is thoroughly dry, apply floor finish.

**For Removing Sealer:**

Use 32 fl.oz./gallon cold water (250 ml/L), (1:4).

1. Wet floor with **Revelation** solution. Allow to stand 20–30 minutes on the floor depending on the number of coats needed to be removed.  
Follow steps 2–5 above.

Recommended for use with Buckeye’s Patented Action Control System<sup>®</sup> II.

For stripping normal to heavy floor finish buildup: Use the Green Action Lock II Connector<sup>™</sup>.

For removing finish and seal: Use the Grey Action Lock II Connector.

TECHNICAL SPECIFICATIONS	
Total Actives	25.2%
pH Concentrate	11.8 – 12.2
pH (1:10)	10.9 – 11.3
Weight/Gallon	8.57 lb
Flash Point	None to Boiling
Color	Bright Red
Fragrance	Rose Floral
Hard Water Stability (1:80 with 350 ppm hard water)	Clear
Rinsing Properties	Excellent
Freeze-Thaw Stability	Unaffected by Freezing
Foaming Properties	Extremely Low

This product produced under one or more of the following patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341; 5,849,682. Canadian patents 2,056,425; 2,080,352; 2,057,027.

For more information about Revelation, scan this code.

