





Available Packaging

30G

55G

The RipSaw Difference

RipSaw is Buckeye's fast-acting, power stripper! **RipSaw** cuts through your floor finish buildup, and makes the labor intensive task of stripping easier and more manageable. It helps get the job done quicker by reducing the dwell time required, while still removing finish and sealer in one application.

RipSaw also has a unique, built-in Automatic Dilution Indicator (ADI[®])! When diluted at approximately 1:4, the stripper solution will turn cloudy. This allows you to achieve the desired dilution ratio while not "over-using" your floor stripper.

RipSaw is designed to be used on all hard floor surfaces. **RipSaw**'s mild aroma makes it pleasant to use. No artificial fragrances have been added.



FEATURES

- Fast-acting
- Low odor
- Low foaming
- Compensates for poor rinsing
- Works in hot or cold water
- Liquefies heavily burnished finish and sealer

- Contains Liquescent[®] technology for better performance and safety
- Butyl-free (2-butoxyethanol or ethylene glycol monobutyl ether CAS#111-76-2)
- No added fragrance
- Resists clogging of pads



DIRECTIONS FOR USE

(For use in hot or cold water) For removing floor finishes and sealers:

Use 32 fl. oz./gal. cold water (250 mL/L), (1:4).

- 1. Wet floor. Allow to stand 10–25 minutes on the floor depending on the number of coats needed to be removed..
- 2. Machine scrub.
- 3. Pick up solution.
- 4. Rinse floor at least twice with cold water.
- 5. After floor is dry, apply floor finish.

TECHNICAL SPECIFICATIONS	
Total Actives	34.4 ± 0.2
pH Concentrate	12.6 ± 0.3
рН (1:4)	12.3 ± 0.2
Weight/Gallon	8.83 lb
Flash Point	None to Boiling
Color	Clear
Fragrance	Mild/No fragrance added
Hard Water Stability	Clear
Rinsing Properties	Excellent
Freeze-Thaw Stability	Unaffected by Freezing
Foaming Properties	Low

This product produced under one or more of the following patents: 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341; 5,849,682. Canadian patents 2,056,425; 2,080,352; 2,057,027.

For more information about RipSaw, scan this code.

