

# LUCENT™

## URETHANE FORTIFIED FLOOR FINISH



### Available Packaging



### FEATURES

- Urethane fortified acrylic system
- Designed for resilient and non-resilient floors
- U.L. listed for slip resistance
- Clear, non-yellowing
- Burnishable and non-powdering
- Durable — reduces strip outs
- Outstanding leveling
- Easy application
- Excellent depth of gloss
- Black mark resistant
- Scratch resistance

### The Lucent Difference

**Lucent** is a water-based urethane fortified floor finish designed to beautify and protect resilient and non-resilient floors. Lucent is easy to apply and provides a high gloss, durable, burnishable, slip resistant surface.

### DIRECTIONS FOR USE

#### FLOOR PREPARATION:

1. Strip floor using a Buckeye floor stripper following label directions.
2. After picking up solution, rinse floor.
3. Allow floor to dry before applying **Lucent**.

#### APPLICATION:

1. Use a clean mop and bucket or applicator.
2. Saturate mop, press firmly into wringer to remove excess **Lucent**. Do not wring mop.
3. Apply **Lucent** using an overlapping figure-eight motion.
4. Allow to dry (usually 30 to 40 minutes). Temperature, humidity and air movement affect dry time.
5. Apply additional coats until desired gloss is achieved. Apply no more than four (4) coats in a 24-hour period.
6. Allow **Lucent** to properly cure for 48 hours before scrubbing.

#### MAINTENANCE:

1. Dust mop floor.
2. Damp mop or autoscrub floor as needed, using a Buckeye floor cleaner, following label directions.
3. Top scrub and recoat, as needed.

### TECHNICAL SPECIFICATIONS

pH	7.6 ± 0.2
Weight/Gallon	8.58 lbs
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Slip Resistance	U.L. Classified



For more information about Lucent, scan this code.

