



VERDE[®]

ENVIRONMENTAL FLOOR FINISH




The Verde Difference

Buckeye **Verde** is a Sealer/Finish designed for “green” floor care programs. All aspects of Buckeye Verde meet the most stringent environmental standards without sacrificing product performance.



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

Available Packaging



FEATURES	ADVANTAGES	BENEFITS
Zinc-free	Satisfies low metal waste water requirement	Safe for environment
High gloss	Presents professional image	Draws compliments to maintenance staff
Green Seal* Certified	Meets or exceeds government specs	Environmentally responsible
Non-yellowing	Lengthens time between strip-outs	Saves labor time and cost
Non-powdering	Lengthens time between strip-outs	Saves labor time and cost
Ammonia-free	Pleasant to work with	No harsh odor
U.L. Listed	Reduces slip and fall liability	Provides shiny but safer working surface
Easy to repair and maintain	Marks and scratches buff out easily to save time	Saves labor time and cost

VERDE[®]

ENVIRONMENTAL FLOOR FINISH

DIRECTIONS FOR USE

FLOOR PREPARATION:

1. Strip floor using Buckeye **Penetrate™**, Buckeye's Green Seal certified floor stripper.
2. After picking up solution, rinse floor until no residue remains.
3. Allow floor to dry before applying **Verde**.

APPLICATION:

1. Use a clean mop and bucket.
2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.
3. Apply finish in even coats.
4. Allow each coat to dry, usually 20 to 30 minutes.
5. Apply multiple coats until desired gloss is achieved.

MAINTENANCE:

1. Dust mop floor.
2. Damp mop floor as needed, using Buckeye **Tenacity®**, **True 7™**, or other Buckeye cleaner.
3. Burnish as needed.

Note: Ensure adequate ventilation, especially in confined areas.

TECHNICAL SPECIFICATIONS	
pH	7.6 ± 0.2
Weight/Gallon	8.55 lbs
Leveling	Excellent
Freeze/Thaw Stability	Passes Three Cycles
Removability	Excellent
Drying Time	20–30 Minutes
Black Mark Resistance	Very Good
Film Color	Clear
Slip Resistance	UL Classified



For more information about Verde, scan this code.



BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com