



POLISHED CONCRETE ENHANCER & PROTECTANT




The Legacy Difference

Buckeye **Legacy Polished Concrete Enhancer & Protectant** is a water-based, urethane fortified concrete coating designed to improve the appearance of floors and protect them from tough stains. Vinegar, antifreeze and alcoholic beverage spills will not absorb into the concrete, but instead “bead up” on the surface.

Legacy Polished Concrete Enhancer & Protectant provides a high shine with minimal maintenance, while providing a slip resistant surface.



Available Packaging



FEATURES

- For use on polished concrete floors — Enhances appearance and protects concrete from staining
- Self-leveling — Coats apply easily
- Minimal labor — Only 1-2 coats required
- Exceptional durability — Won't break down under traffic
- Detergent resistant — Holds up under repeated scrubbing or mopping using **Legacy Concrete Cleaner & Conditioner**
- Easily stripped — Using Buckeye **RipSaw™** floor stripper
- Can be burnished — Full Hair pads with a high speed burnisher works best



POLISHED CONCRETE ENHANCER & PROTECTANT

DIRECTIONS FOR USE

FLOOR PREPARATION:

For initial application on polished concrete floors:

- 1. Dust mop.
2. Strip the floor using Buckeye RipSaw stripper at a 1:4 dilution.
3. Thoroughly rinse floor with plain water. Scrubbing with clean pads or a brush during this step is also recommended.
4. Allow floor to fully dry before applying 2 coats of Legacy.

APPLICATION (1500 sq. ft./gallon):

- 1. Apply with an E-Z Way Applicator K-100, a 3/8" nap paint roller, a synthetic finish mop, or a Flat Mopping System.
2. If using a synthetic mop, saturate synthetic finish mop and press firmly into wringer to remove excess Legacy. Do not wring mop.
3. Apply Legacy using an overlapping figure-eight motion. Note: The first coat on porous floors should be applied medium to heavy. Moving slowly with the mop head is advised.
4. Allow to dry until it is totally tack free (usually 1 hour). Temperature, humidity and air movement affect dry time.
5. Apply one additional coat after floor has fully dried.
6. Allow Legacy to properly cure for 48 hours before autoscrubbing.

DAILY MAINTENANCE:

- 1. Dust mop floor.
2. Damp mop or autoscrub floor, using Buckeye Legacy Concrete Cleaner & Conditioner at 1 oz./gallon of water.

ANNUAL/AS NEEDED MAINTENANCE:

To maintain protection from spills and staining:

- 1. Dust mop floor.
2. Double scrub concrete using a blue pad and Buckeye Legacy Concrete Cleaner & Conditioner diluted at 1 oz./gallon of water.
3. Rinse the floor with clear water and let dry.
4. Apply 1 coat of Legacy. 2 coats may be needed in high traffic areas and areas at risk of staining from spills.

AS NEEDED RESTORATIVE MAINTENANCE:

- 1. Dust mop floor.
2. Strip the floor using Buckeye RipSaw stripper at a 1:4 dilution. LEGACY DOES NOT STRIP LIKE CONVENTIONAL FLOOR FINISHES, but is easily stripped with RipSaw. Legacy does not emulsify/liquefy like typical Buckeye floor finishes — instead it crinkles up and is easily removed from the concrete floor by the action of a stripping pad or brush. High performance, open weave stripping pads or brushes are recommended for easy rinse and reuse.
3. Thoroughly rinse floor with plain water. Scrubbing with clean pads or a brush during this step is also recommended.
4. Allow floor to fully dry before applying 2 coats of Legacy using a standard synthetic finish mop.

Note: Do not put used product back into its original container!

Note: Not recommended for kitchen floors or on floors that remain wet for long periods of time.

Table with 2 columns: Property and Value. Rows include pH Concentrate (9.2 ± 0.2), Leveling (Excellent), Freeze/Thaw Stability (Passes 3 cycles), Removability (Excellent), Drying Time (1-2 hours), Black Mark Resistance (Excellent), Film Color (Opaque White), Scrubability (Excellent), Weight/Gallon (8.68 lbs), Slip Resistance (U.L. Classified).



BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com